



DL32 DIGITAL LEVEL

Professional performance at an affordable price.

- Fast, easy and accurate
- High precision
- Self-levelling

Designed with durability.

- Water-resistant housing
- Compensator lock for secure transport

Proven Simplicity.

- Single button operation
- Easy access battery compartment
- Elevation and height difference measurement
- Large internal memory

Product Specifications.

Electronic measurement

- 1.Height accuracy: 1.5mm/km (standard staff)
0.7mm/km (high accuracy staff)
- 2.Ranging distance: 3 to 110m (subject to environmental conditions)

Optical Measurement

- 2.Folding bar code staff: 1.5mm

Minimum display unit

- 4.Height measurement: 1mm/0.01mm
- 5.Distance measurement: 0.01m
- 6.Measurement speed: 3 seconds

Telescope

- 7.Magnification: 32 X
- 8.Objective lens aperture: 40mm
- 9.Working range: $\pm 12'$
- 10.Accuracy: $\pm 0.3''$
- 11.Bubble precision: 8'/2mm
- 12.Display: 128(width)*64(height); pixel with light
- 13.Battery: 4x 1.2V rechargeable batteries, continuous use for 10 hrs
- 14.Working temperature: -20°C - +50°C

Package options available.

Hard carry case, 4x AAA batteries, plumb bob and manual
Warranty: 1 year

